

TECHNICAL DATA SHEET



FEATURES & BENEFITS

- Fast reacting
- Easy to use cartridges
- No mixing
- Self contained packaging
- Non Hazardous
- No shrinkage
- Expands 10 times liquid

PRODUCT DATA

- VOC content: 0%
- Color: Amber
- Specific gravity: 1.06 B side, 1.23 A side
- Reaction time: 3-5 s
- Expansion time: 30 s

MIX RATIO

1 to 1 by volume

PACKAGING

Depending on Formulation:

- I-2410, I-2460: Cartridge
- I-1160: Cartridge, 5 gal. bucket
- I-1190: 5 gal. bucket, 55 gal drum, tote

* The values stated in inch-pound units are to be regarded as the standard. The values given in International System are for information only.



REPAIR
MATERIALS



Rapid-Setting Grouts for Heavy Infiltration & Leak Stoppage

DESCRIPTION

Maverick I & I hydrophilic and hydrophobic polyurethane foams are designed to stop active infiltration and exfiltration at the source. These single and dual-component systems deliver controlled expansion, fast reaction, and strong adhesion in wet environments.

APPLICATIONS

- Sealing joints
- Cracks
- Penetrations
- Soil-to-structure interfaces in critical infrastructure

FORMULATIONS

- I-2410: Point repair foam
- I-2460: 60 second point repair foam
- I-1190: Hydrophilic single component foam
- I-1160: Variable speed, hydrophilic single component foam

SAFETY

Always use safety glasses and protective clothing including gloves when using this product.

STORAGE

Store between 40°F | 4.4°C and 100°F | 37.8°C.

DISPOSAL

Dispose of cartridge in adherence with local regulations.