

QUICK-PLUG

FAST SETTING CEMENTITIOUS WATERSTOP

DESCRIPTION: Quick-Plug is a blend of special cements and admixtures which are designed to instantly stop running water or seepage in all types of concrete and masonry structures.

PACKAGING: Quick-Plug is supplied in a 50 lb. | 11.34 kg. plastic pail.

YIELD:

Quick-Plug will yield approximately 0.49 cu. ft. | 0.014 cu. m. per pail.

APPLICATION INFORMATION:

To Seal Running Water or Leaks

Prepare crack or hole by chipping out loose material to a minimum depth and width of 0.75 in. | 19.05 mm. Using a rubber gloved hand, place a generous amount of dry Quick-Plug to active leak and maintain external pressure for 60 seconds. Repeat until leak stops.

WARRANTY:

A member of the Vortex family of companies, Parson Environmental warrants its products to be free of defects in material and workmanship. Unless superseded by project specifications and terms agreed upon in writing between installer and Parson Environmental prior to bid, if within one year from purchase, any Parson Environmental product is proven defective, the company will replace said product or refund its purchase price at its sole discretion. The company's obligation shall be limited solely to such replacement or refund. There are no other warranties by Parson Environmental, expressed or implied. There is no warranty if Parson Environmental products are used contrary to Parson Environmental's written directions.

PRECAUTIONS:

Avoid eye contact or prolonged contact with skin. Wash thoroughly after use. Persons using Quick-Plug should wear necessary eye protection, dust mask and rubber gloves. Read all product labels and technical literature.

TYPICAL PERFORMANCE

CHARACTERISTICS*:

- Compressive Strength (ASTM C39)
24 hr. >1000 psi | 6.90 MPa
- Bond Strength (ASTM C882)
28 day >500 psi | 3.45 MPa

** The values stated in inch-pound units are to be regarded as the standard. The values given in International System are for information only.*

RECOMMENDED FOR:

- Sewer Pipes and Manholes
- Concrete Tanks
- Elevator Pits
- Cisterns
- Basements
- Concrete & Masonry Walls

FEATURES AND BENEFITS:

- Stops running water immediately
- Non-Shrink, expands as it sets
- Contains no calcium chloride
- Non-Metallic
- Sulfate resistant
- Easily applied
- No Mixing



17 AD Asbury Rd.
Greenville, SC 29605
(800) 356-9023
info@parsonenvironmental.com
www.parsonenvironmental.com