



sprayMASTER[®] XL

Non-CDL Manhole Rehabilitation Truck

WHY PULL IT, WHEN YOU CAN DRIVE IT!

The sprayMASTER manhole rehabilitation truck is a game-changer and eliminates the need to haul your mobile mortar plant on a trailer. It's a Class 6, non-CDL vehicle, and comes in just under 26,000 lbs. fully loaded with crew, materials, tools, and water.

COMFORTABLE, COMPACT, & CONVENIENT

The Vortex sprayMASTER truck is ergonomically designed for crew comfort and efficient manhole rehabilitation. Built on an F-650 (or equal) with a roomy 4-door cab, your crew will travel in comfort to and from the jobsite.

TRUCK & CHASSIS FEATURES

- 4-door, 4-passenger cab
- Diesel engine, automatic transmission
- 65 gallon fuel tank
- Wide view mirrors
- Twin stacked 24" x 84" heavy duty lockable metal storage lockers for tools, CSE, PPE, and other supplies
- Under frame supply storage
- Class 6, non-CDL vehicle





All manhole rehabilitation components operate independently and does not rely on the truck for power, air, hydraulics, fuel, or any other controls.

**Roll-up
Ready!**

TRUCK SPECS

- Cab and Chassis Model: Ford F-650
- **Wheelbase (WB)**
 - 278 in. | 23.17 ft.
 - Front axle to rear axle
- **Cab to Axle (CA)**
 - 174 in. | 14.50 ft.
 - Back of truck cab to rear axle
- **Cab to End of Frame (CE)**
 - 276 in. | 23.00 ft.
 - Back of truck cab to rear of frame
- **Axle to End of Frame (AE)**
 - 106 in. | 8.83 ft.
 - Rear axle to rear of frame
- **Overall Length (OAL)**
 - 432 in. | 36.00 ft.
 - Bumper to bumper
- Base Build: GVWR
- OEM: 26,000
- Front Axle GAWR: 8,500
- Rear Axle GAWR: 17,000

sprayMASTER TRUCK MOUNTED MORTAR PLANT FEATURES

- **Self-Contained Power Pack**
 - 49HP Kubota diesel engine / hydraulic power plant
 - 6,500w generator with GFCI protection
 - 20 gallon diesel fuel capacity
 - 29CFM @ 90 psi air compressor
 - 5,000 psi @ 3.5 gpm pressure washer
 - 40 psi @ 9 gpm hydraulically driven water transfer pump
- **Pump and Mixer**
 - 84 gallon (30" diameter) mixing hopper with paddle mixer
 - 25 gallon holding hopper
 - Progressive cavity 3-stage pump 8gpm @ 500 psi
 - Mixing skid configured to be removable with quick pins & fork pockets
- **Water Tank**
 - 250 or 400 gallon capacity, polyethylene
 - 1 1/2" fill with inline screen accessible from street level
 - Water tank gauge visible from street
 - Drain valve at bottom of tank
 - Flood suction to pressure washer with inline filter
- **Work Platform**
 - Non-slip platform
 - Built-in steps/ladder
 - Hand holds for three points of contact