

# MaxLiner Resin Saturation Chart

Recommended Resin Saturation Rates for  
MaxLiner® Liners with MaxPox® Resin Systems

## MAX WOVLINER®

Minimum Gap Setting =  $T \times 2 + 2\text{mm}$

2.5MM (AVAILABLE IN 2" AND 3" ONLY)			3.5MM
2"	0.25	—	—
3"	0.25	—	0.70
4"	—	—	0.80
5"	—	—	1.00
6"	—	—	1.20
8"	—	—	1.60

## MAX WOVOX® & WOVOGLASS®

Minimum Gap Setting =  $T \times 2 + 2\text{mm}$

2.5MM			3.5MM
2"	0.30	—	—
3"	—	—	0.75
4"	—	—	0.90
6"	—	—	1.30
8"	—	—	1.70

## MAX SCRIM LINER & LINERTUBE®

Minimum Gap Setting =  $T \times 2 + 2\text{mm}$

		3MM	4.5MM
3"	—	0.56	—
4"	—	0.75	1.00
5"	—	0.93	1.30
6"	—	1.10	1.50
8"	—	1.50	2.00
10"	—	1.65	2.50

# TECHNICAL DATA SHEET



## MAXLINER FLEX 4D

Minimum Gap Setting =  $T \times 2 + 1\text{mm}$  (+ 2mm for transition)

			4.5MM
3"	—	—	0.85
4"	—	—	1.10
6"	—	—	1.50
8"	—	—	2.00
10"	—	—	3.00

## MAX FLEXLINER

Minium Gap Setting =  $T \times 1 + 1\text{mm}$

		3MM	4.5MM
4"	—	0.75	1.00
5"	—	0.85	1.30
6"	—	0.90	1.50

## MAX SUPERFLEX® D

(Minimum Gap Setting =  $T \times 2 + 1\text{mm}$ )

	2MM		4.5MM
2"	0.25	—	—
3"	0.35	—	.90
4"	0.45	—	1.25
5"	—	—	1.50
6"	—	—	1.75
8"	—	—	2.50
10"	—	—	3.00

## TECHNICAL SUPPORT

Call technical support with additional questions at (877) 426-5948.

## DISCLAIMER

The information contained herein is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and no warranty of any kind is made with respect thereto. Exact coating type and thickness depend on the specific types of resin being used. Always read, understand, and comply with hazard warnings described in the products' Safety Data Sheet(s) before use.