

**Safety Data Sheet
Max VertiPox Resin****Revision Date:
15 July, 2026****Section 1. Identification****Product identifier**

Product Identity	Max VertiPox Resin
Other means of identification	Not Applicable
Relevant identified uses of the substance or mixture and uses advised against	100% solids epoxy resin system for cured-in-place pipe (CIPP) lining and trenchless pipe rehabilitation.

Details of the supplier of the safety data sheet

Company Name	MaxLiner 7606 Whitehall Executive Center Dr. Suite 400 Charlotte, NC 28273
---------------------	--

Emergency

24 hour Emergency Telephone No.	24-Hour Emergency Contact: (Infotrac) 1-800-535-5053 Local Emergency Contact: 1-800-535-5053
Customer Service:	877-426-5948

Section 2. Hazard(s) identification**Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)**

Skin corrosion/irritation category 2;H315	Causes skin irritation.
Serious eye damage / eye irritation, category 2A;H319	Causes serious eye irritation.
Skin sensitizer category 1;H317	May cause an allergic skin reaction.
Aquatic toxicity (chronic), category 2;H411	Toxic to aquatic life with long lasting effects.

Label elements**Warning**

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

[Prevention]

- P261 Avoid breathing dust, fume, gas, mist, vapors, spray.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves, eye protection, and face protection.

[Response]

- P302+352 IF ON SKIN: Wash with plenty of soap and water.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+313 If skin irritation or a rash occurs: Get medical advice or attention.
- P337+313 If eye irritation persists: Get medical advice or attention.
- P362+364 Take off contaminated clothing and wash it before reuse.
- P391 Collect spillage.

[Storage]

No GHS storage statements

[Disposal]

- P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

- This product contains no PBT/vPvB/vPvM chemicals.
- This product contains no endocrine disrupting chemicals.
- Does NOT contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the US EPA PFASMASTER combined list of PFAS chemicals.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA’s Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Diglycidyl ether of bisphenol A CAS Number: 25068-38-6 Synonyms: Epoxy Resin	65 - 85	Serious eye damage / eye irritation, category 2;H319: C ≥ 5 % Skin corrosion/irritation category 2;H315: C ≥ 5 % Skin sensitizer category 1;H317 Aquatic toxicity (chronic), category 2;H411	No data available
Bisphenol F epoxy resin CAS Number: 28064-14-4 Synonyms: Bisphenol F nhựa epoxy (av.mol.wt<700)	7 - 13	Skin corrosion/irritation category 2;H315 Serious eye damage / eye irritation, category 2;H319 Skin sensitizer category 1;H317 Aquatic toxicity (chronic), category 2;H411	No data available
Alkyl(C12-C14)glycidyl ether CAS Number: 68609-97-2 Synonyms: Alkyl (C12-14) glycidyl ether	7 - 13	Skin corrosion/irritation category 2;H315 Skin sensitizer category 1;H317	No data available
Amorphous silica, hydrophobic CAS Number: 67762-90-7 Synonyms: Silicones and siloxanes, dimethyl-, reaction products with silica	0.5 - 1.5	Not Classified	No data available

The actual concentration or concentration range is withheld as a trade secret.
*PBT/vPvB - PBT, vPvM or vPvB-substance.
The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Most important symptoms and effects, both acute and delayed	
Overview	No specific symptom data available. No chronic toxicity or long term toxicity information available. Treat symptomatically. See section 2 for further details.
Eyes	Causes serious eye irritation.
Skin	May cause an allergic skin reaction. Causes skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: Carbon monoxide, carbon dioxide, aldehydes, and various compounds from incomplete combustion.

Avoid breathing dust, fume, gas, mist, vapors, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

At higher temperature vapors can cause pressure buildup in sealed containers. Use water to cool containers exposed to fire. Self-contained respirator equipment and full protective clothing required when smoke or fumes are generated. Electrical grounding not recommended.

ERG Guide No. 171

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed

containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong acids, strong bases. Amines and mercaptans may initiate possible hazardous polymerization.

See section 2 for further details. - [Storage]

Specific end use(s)

100% solids epoxy resin system for cured-in-place pipe (CIPP) lining and trenchless pipe rehabilitation.

Section 8. Exposure controls / personal protection

Control parameters

		Exposure Limits	
CAS No.	Ingredient	Source	Value
25068-38-6	Diglycidyl ether of bisphenol A	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
28064-14-4	Bisphenol F epoxy resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
67762-90-7	Amorphous silica, hydrophobic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
68609-97-2	Alkyl(C12-C14)glycidyl ether	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.

Skin

Avoid skin contact. Wear PVC or rubber gloves to keep skin contact to a minimum. Refer to the manufacturer's recommendations regarding the suitability of any gloves used.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	No available information
Odor	No available information
Odor threshold	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	No available information
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available information Upper Explosive Limit: No available information
Flash Point	No available information
Auto-ignition temperature	No available information
Decomposition temperature	No available information
pH	No available information
Viscosity (cSt)	No available information
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa)	No available information
Relative Density	No available information
Vapor Density	No available information
Evaporation rate (Ether = 1)	No available information
Oxidising properties	No available information
Explosive properties	No available information
Other information	No other relevant information.

Section 10. Stability and reactivity**Reactivity**

Hazardous polymerization may occur if product is not handled as per instructions.

Chemical stability

This product requires another product to react at room temperature. Mix and use product in accordance with directions for safety. Excessive heat and fume generation can occur if improperly handled. Not sensitive to mechanical impact.

Possibility of hazardous reactions

No available information

Conditions to avoid

Avoid high temperatures and contact with incompatible material

Incompatible materials

Strong acids, strong bases. Amines and mercaptans may initiate possible hazardous polymerization.

Hazardous decomposition products

Carbon monoxide, carbon dioxide, aldehydes, and various compounds from incomplete combustion.

Section 11. Toxicological information

Acute toxicity

Based on the properties of the epoxy constituents and considering toxicological data on similar preparations this preparation may be an irritant and a skin and respiratory sensitizer. Low molecular weight epoxy constituents are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and sensitization, possibly with cross-sensitization to other epoxies. Skin contact with the preparation and exposure to spray mist and vapor should be avoided.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Diglycidyl ether of bisphenol A - (25068-38-6)	> 5,000.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Bisphenol F epoxy resin - (28064-14-4)	No data available.	No data available.	No data available.	No data available.	No data available.
Alkyl(C12-C14)glycidyl ether - (68609-97-2)	No data available.	No data available.	No data available.	No data available.	No data available.
Amorphous silica, hydrophobic - (67762-90-7)	No data available.	> 2,000.00, Rat - Category: NA	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
25068-38-6	Diglycidyl ether of bisphenol A	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
28064-14-4	Bisphenol F epoxy resin	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
67762-90-7	Amorphous silica, hydrophobic	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
68609-97-2	Alkyl(C12-C14)glycidyl ether	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable

Aspiration hazard	---	Not Applicable
-------------------	-----	----------------

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

No specific symptom data available.

No chronic toxicity or long term toxicity information available. Treat symptomatically.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction. Causes skin irritation.

Section 12. Ecological information

Toxicity

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Diglycidyl ether of bisphenol A - (25068-38-6)	3.10, Pimephales promelas	1.40, Daphnia magna	No data available.
Bisphenol F epoxy resin - (28064-14-4)	9.00, Oncorhynchus mykiss	9.00, Daphnia magna	No data available.
Alkyl(C12-C14)glycidyl ether - (68609-97-2)	No data available.	No data available.	No data available.
Amorphous silica, hydrophobic - (67762-90-7)	> 5,000.00, Fish	> 5,000.00, Daphnia magna	> 5,000.00, Algae

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

Not regulated for packages under 5L (1.3 gallons) or 5.0 kg (11 lbs).



	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)	Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)	Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)
Transport hazard class(es)	Class: 9 Sub Class: Not Applicable	Class: 9 Sub Class: Not Applicable	Class: 9 Sub Class: Not Applicable
Packing group	III	III	III
Environmental hazards	IMDG Marine Pollutant: Yes; (Diglycidyl ether of bisphenol A)		
Special precautions for user	No available information		

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Classification of the substance or mixture under OSHA’s Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0000108-65-6	2-Methoxy-1-Methylethyl Acetate	Yes	PMN	ACTIVE
0068609-97-2	Alkyl(C12-C14)glycidyl ether	Yes	UVCB TP	ACTIVE
0067762-90-7	Amorphous silica, hydrophobic	Yes	UVCB XU	ACTIVE
0028064-14-4	Bisphenol F epoxy resin	Yes	UVCB XU	ACTIVE
0000147-14-8	Blue pigment	Yes		ACTIVE
0000112-02-7	Cetrimonium chloride	Yes		ACTIVE
0028901-96-4	Cuprate(1-), [29h,31h-phthalocyanine-c-sulfonato(3	Yes		ACTIVE
0025068-38-6	Diglycidyl ether of bisphenol A	Yes	XU	ACTIVE
0000123-86-4	N-Butyl Acetate	Yes		ACTIVE
0001312-76-1	Potassium silicate	Yes		ACTIVE
Proprietary	Trade Secret	Yes		ACTIVE
0001330-20-7	Xylene	Yes		ACTIVE

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Cuprate(1-), [29h,31h-phthalocyanine-c-sulfonato(3

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Revision Date 15 July, 2026

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Disclaimer: The information presented herein is supplied as a guide to those who handles or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document